

The Roton pendant makes an impressive design statement in the simplicity and scale of its cylindrical geometry. Featuring a spun aluminum body and subtle diffuser, the Roton pendant houses a powerful LED light source designed to deliver softly diffused down lighting for controlled and distinctive illumination.

## Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized lensing
- IP-65 Rated

## Adjustable distance from ceiling

## **SPECIFICATIONS**

DELIVERED LUMENS	2556
WATTS	36
VOLTAGE	Universal 120-277V
DIMMING	0-10, ELV, TRIAC
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Ceiling
ADJUSTABILITY	Adjustable stem length (3", 6" and 12"). Integrated ball joint that accommodates sloped ceiling up to 45°.
CCT	2700K, 3000K or 4000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B1-U2-G1
DARK SKY	Non-compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years


<sup>\*</sup> Visit techlighting.com for specific warranty limitations and details.



# ORDERING INFORMATION

700OPROT	CRI / CCT		WIDTH		FINISH		VOLTAGE	
	927	90 CRI, 2700K	18	18"	Z	BRONZE	UNV	120V-277\
	930	90 CRI, 3000K			Н	CHARCOAL		
	940	90 CRI, 4000K			В	BLACK		

RIGID STEM ONLY (ADJUSTABLE 3", 6" AND 12" LENGTHS)



Roton Pendant

## PHOTOMETRICS\*

\*For latest photometrics, please visit www. techlighting.com/OUTDOOR

#### **ROTON 18**

Total Lumen Output: 2556


Total Power: 36

Luminaire Efficacy: 71

Color Temp: 4000K

CRI: 90+

BUG Rating: B1-U2-G1



## PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES



**GENERATION** BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500