

MODEL DESCRIPTION

HousePure® Secure Tankless Water Heater Protection Part # WI-HP-SECURE-.75L (water entry left side) Shipping Wt: 7 lbs.
 Part # WI-HP-SECURE-.75R (water entry right side)
 Utilizing Siliphos Polyphosphate
 Recommended for all Tankless Water Heater Manufacturers



LEVEL 1 Tankless Water Heater Scale Prevention. Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A 5-micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations. Features a 3/4" NPT inlet/outlet with a differential filter-change gauge for peace-of-mind.

Includes mounting bracket, filter-change indicator gauge & filter-change spanner wrench

Max Descaling Service Flow Rate: 9 gallons/minute

Dimensions: Width: 5.25" Height: 25.75" Depth: 5.5"

Filter Capacity: One year or when gauge or timer indicates change needed

Water Temperature Range: 40°F to 100°F

Tools Required: Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings and inlet gate valve



NEW
 Water entry RIGHT side
WI-HP-SECURE-.75R

Water, Inc filter change indicator included
 Component Tested to NSF/ANSI Standard 42 for material requirements.

NEW
 Water entry RIGHT side
WI-HP-SECURE-.75R

HousePure® Secure Replacement Cartridge Part # WI-HP-SECURE-.75C Shipping Wt: 1 lbs.
 Utilizing Siliphos Polyphosphate Shipping Wt: 19 lbs.
 Recommended for all Tankless Water Heater Manufacturers



Capacity: One year or when gauge indicates change needed

Dimensions: Height: 20" Diameter: 2.5"

Replacement Cartridge for HousePure® Secure 3/4" tankless water heater filter system. The 5-micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

The HousePure® Secure cartridge should be changed annually or when gauge indicates a change is needed sooner.

Tested to NSF/ANSI Standard 42 for material requirements.

Water, Inc filter change indicator included



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)