# WATERWORKS

HNLS<sub>20</sub> **HENRY** 

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



SHOWN IN HENRY GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES HNLS20

## **INSPIRATION**

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

#### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 1 5/8'

Deck Thickness Minimum: 3/16"

Drain Depth Maximum: 25/8"

Drain Hole Diameter: 1 3/4" Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 1/4"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 12"

Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn

Depth / Width: 7 13/16"

Drain Depth Minimum: 3/8"

Height: 9"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Inlet Supply Spread Maximum: 12"

Inlet Supply Spread Minimum: 8"

Installation Type: Deck Mounted

Integrated Diverter: N

Integrated Spray: N

Number of Handles: Two

Number of Holes: Three Hole Primary Material: Brass

Spout Swivel: N

Spray Included in Unit: N

Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

### **CODES & STANDARDS**

Code # HNLS20X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

### **PRODUCT FEATURES**

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Brass material is used for components

Standard flow rate is 2.2qpm (8.3 L/min) and State of California requires 1.2qpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

### **CERTIFICATIONS**



HENRY HNLS20

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

